

LA-UR- 04-0838

Approved for public release;
distribution is unlimited.

Title: ANOMALOUS MASS TRANSPORT IN AU/304 STAINLESS
POWDER UNDER SHOCK LOADING

Author(s): KARL P. STAUDHAMMER

Submitted to: FIFTH PACIFIC RIM INTERNATIONAL CONFERENCE
ON ADVANCED MATERIALS AND PROCESSING,
BEIJING, CHINA, NOVEMBER 2-5, 2004



Los Alamos National Laboratory, an affirmative action/equal opportunity employer, is operated by the University of California for the U.S. Department of Energy under contract W-7405-ENG-36. By acceptance of this article, the publisher recognizes that the U.S. Government retains a nonexclusive, royalty-free license to publish or reproduce the published form of this contribution, or to allow others to do so, for U.S. Government purposes. Los Alamos National Laboratory requests that the publisher identify this article as work performed under the auspices of the U.S. Department of Energy. Los Alamos National Laboratory strongly supports academic freedom and a researcher's right to publish; as an institution, however, the Laboratory does not endorse the viewpoint of a publication or guarantee its technical correctness.

Form 836 (8/00)

Abstract to be submitted for the Fifth Pacific Rim International Conference on Advanced Materials and Processing, Beijing, China, November 2-5, 2004

Invited paper in session [T] Layered and Graded Materials; Combustion Synthesis

Anomalous Mass Transport in Au/304 Stainless Steel Powder Under Shock Loading

Karl P. Staudhammer

Los Alamos National Laboratory, Nuclear Materials Technology Division, PO Box 1663, MS E 504, Los Alamos, New Mexico, 87545, U. S. A.

Abstract

Dynamic deformation experiments on gold plated 304L stainless steel powders were undertaken using a axial symmetrical implosion geometry. These experiments utilized pressures of 0.08 to 1.0 Mbar and contained a symmetric radial melt region along the central axis of the sample holder. To understand the role of deformation in a porous material, the pressure, and temperature as well as the deformation heat and associated defects must be accounted for. Using a strain controllable shock loading design it was possible to separate and control independently strain and pressure. Thus enabling the ability to control the added heat from the deformation process undergoing compaction/consolidation of the powder. When the added heat of consolidation deformation exceeds the melt temperature of the 304 powders, a melt zone results that can consume large regions of the compact. It is within these regions that very high diffusion of gold into the powder occurs. These anomalous increases have been observed via optical microscopy, scanning electron microscopy and EDAX measurements. Values exceeding 1200 m/sec have been measured and correlated to the powder sizes, size distribution and packing density, concomitant with sample container strains ranging from 2.0% to 26%.